

1.	PRODUCT SPECIFICATIONS			
1.1.	Project Number	PJ1401	Product name: PIX 600	Code: EPX0640DFBL00018 000
1.2.	Product Type	Indoor and outdoor Led waterproof ceiling light		
1.3.	Applications	Indoor parking lots - Supermarkets - Stowage areas - Workplaces		
1.4.	Image			

2.	MAIN FEATURES	
2.1.	Dimensions	540x80x70mm
2.2.	Weight	0,7 Kg
2.3.	Operating temperature	- 20°C / + 40°C
2.4.	Storage temperature	- 30°C / + 50°C
2.5.	Optical Group	• Source color temperature • Led 4000K • CRI ≥ 80 • LED luminous efficiency: 155.5 Lm/W
2.6.	Linking o	75 units (Continuous row connection)

3.	REGULATORY REFERENCES	
3.1.	Approval	     Low Flicker
3.2.	Degree of protection	IP 65
3.3.	Insulation Class	CLASS I
4.	ELECTRICAL CHARACTERISTICS	
4.1.	Power Supply	220-240 Vac 50/60Hz
4.2.	Nominal Power	18 W +/-10%
4.3.	Power Supply Unit	Driver included
4.4.	Power Cord	Ø est. da 5mm a 12mm

Date	Verified by	Approved by	Page 1 of 2
24/11/2023			

**EP S.P.A.**

Via Del Commercio, 1 25039 Travagliato (BS) Italy
ph. +39 030 258 39 90 fax +39 0302584012
Cap. Soc. € 1.000.000,00 i.v.
VAT: IT 03384740175


**TECHNICAL
DATASHEET**

5.	MATERIALS	
5.1.	Body	Self-extinguishing polycarbonate technopolymer, Anti-yellowing
5.2.	Diffuser	Optical polycarbonate
5.3.	Gasket	Expanded silicon
5.4.	Hooks for wall mount and suspension	Stainless steel AISI 304
5.5.	Colour	Gray

6.	WARRANTY	
6.1.	Optical Group Life	≥50.000 hr L80B10
6.2.	Warranty	5 Years

7.	PHOTOMETRIC CHARACTERISTICS	
7.1.	Light source output	3050 lumen (face value) Ta=25°C
7.2.	Fitting output	2800 lumen +/-7%
7.3.	Type of optics	Diffusing

8.	PHOTOMETRIC CURVES	
----	--------------------	--



C0 / C180 C90 / C270

Date	Verified by	Approved by	Page 2 of 2
24/11/2023			