

1.	PRODUCT SPECIFICATIONS		
1.1.	Project Number	PJ1123	Product name: ELLISSE 1200 Code: EEL1240LUBL20040
1.2.	Product Type	Indoor and outdoor Led waterproof ceiling or suspended light	
1.3.	Applications	Indoor parking lots - Supermarkets - Stowage areas - Workplaces	
1.4.	Image		

2.	MAIN FEATURES	
2.1.	Dimensions	1272x110x53 mm
2.2.	Weight	1,78 Kg
2.3.	Operating temperature	- 20°C / + 40°C
2.4.	Storage temperature	-30°C / + 50°C
2.5.	Optical Group	☐ Source color temperature ☐ Led 4000K ☐ CRI ≥ 80 ☐ LED luminous efficiency: 150 Lm/W

3.	REGULATORY REFERENCES	
3.1.	Approval	     Low Flicker
3.2.	Degree of protection	IP 65
3.3.	Insulation Class	CLASSE II
4.	ELECTRICAL CHARACTERISTICS	
4.1.	Power Supply	220-240 Vac 50/60Hz
4.2.	Nominal Power	40 W +/-10%
4.3.	Power Supply Unit	Driver included
4.4.	Power Cord	Øest. da 5mm a 12mm

**EP S.r.l.**

Via Del Commercio, 1 25039 Travagliato (BS) Italia
ph. +39 030 258 39 90 fax +39 0302584012
Cap. Soc. € 1.000.000,00 int.
VAT: 04678140981


**TECHNICAL
DATASHEET**

5.	MATERIALS	
5.1.	Body	Self-extinguishing polycarbonate technopolymer, Anti-yellowing
5.2.	Diffuser	Optical polycarbonate
5.3.	Gasket	Expanded silicon
5.4.	Hooks for wall mount and suspension	Stainless steel AISI 304
5.5.	Colour	Grey RAL 7035

6.	WARRANTY	
6.1.	Optical Group Life	≥50.000 hr L70B20
6.2.	Warranty	2 years

7.	PHOTOMETRIC CHARACTERISTICS	
7.1.	Light source output	6000 lumen (face value) Ta=25°C
7.2.	Fitting output	5552 lumen +/-7%
7.3.	Type of optics	Diffusing

8.	PHOTOMETRIC CURVES	
----	--------------------	--



C0 / C180 C90 / C270

Date	Verified by	Approved by	Page 2 of 2
24/09/2026			