


1.	PRODUCT SPECIFICATIONS			
1.1.	Project Number	PJ1401	Product name: PIX 1500	Code: EPX1540DFBL00052 000
1.2.	Product Type	Indoor and outdoor Led waterproof ceiling light		
1.3.	Applications	Indoor parking lots - Supermarkets - Stowage areas - Workplaces		
1.4.	Image			

2.	MAIN FEATURES	
2.1.	Dimensions	1450mm X 80mm X 70mm
2.2.	Weight	1,6Kg
2.3.	Operating temperature	- 20°C / + 40°C
2.4.	Storage temperature	- 30°C / + 50°C
2.5.	Optical Group	☐ Source color temperature ☐ Led 4000K ☐ CRI ≥ 80 ☐ LED luminous efficiency: 146 Lm/W
2.6.	Linking	25 units (Continuous row connection)

3.	REGULATORY REFERENCES	
3.1.	Approval	     Low Flicker
3.2.	Degree of protection	IP 65
3.3.	Insulation Class	CLASS I
4.	ELECTRICAL CHARACTERISTICS	
4.1.	Power supply	220-240 Vac 50/60Hz
4.2.	Nominal Power	52 W +/-10%
4.3.	Power supply unit	Driver included
4.4.	Power Cord	Øest. from 5mm to 12mm

Date	Verified by	Approved by	Page 1 of 2
24/11/2023			

**EP S.r.l.**

Via Del Commercio, 1 25039 Travagliato (BS) Italia
ph. +39 030 258 39 90 fax +39 0302584012
Cap. Soc. € 1.000.000,00 int.
VAT: 04678140981


**TECHNICAL
DATASHEET**

5.	MATERIALS	
5.1.	Body	Self-extinguishing polycarbonate technopolymer, Anti-yellowing
5.2.	Diffuser	Optical polycarbonate
5.3.	Gasket	Expanded silicone
5.4.	Hooks for wall mount and suspension	Stainless steel AISI 304
5.5.	Colour	Gray

6.	WARRANTY	
6.1.	Optical Group Life	≥50.000 hr L80B10
6.2.	Warranty	2 years

7.	PHOTOMETRIC CHARACTERISTICS	
7.1.	Light source output	7.800 lumen (face value) Ta=25°C
7.2.	Fitting output	7.600 lumen +/-7%
7.3.	Type of optics	Diffusing

8.	PHOTOMETRIC CURVES	
----	--------------------	--

C0 / C180C90 / C270

Date	Verified by	Approved by	Page 2 of 2
24/11/2023			