

1.	PRODUCT SPECIFICATIONS			
1.1.	Project Number	PJ1427	Product name: QUADRA50 600	Code: EQD06T0DFPS10018000 (WHITE) Code: EQD06T0DFPS30018000 (BLACK)
1.2.	Product Type	Linear LED lighting for indoor use		
1.3.	Applications	Indoor area		
1.4.	Image			

2.	MAIN FEATURES	
2.1.	Dimensions	600x50x50 mm
2.2.	Weight	0,6 Kg
2.3.	Operating temperature	- 20°C / + 40°C
2.4.	Storage temperature	-30°C / + 50°C
2.5.	Optical Group	☐ Source color temperature ☐ Led 3000K – 4000K – 6500K (CCT) ☐ CRI ≥ 80 ☐ LED luminous efficiency: 155 Lm/W

3.	REGULATORY REFERENCES	
3.1.	Approval	   Low Flicker
3.2.	Degree of protection	IP 20
3.3.	Insulation Class	CLASS I
4.	ELECTRICAL CHARACTERISTICS	
4.1.	Power Supply	220-240 Vac 50/60Hz
4.2.	Nominal Power	Power selector - from 10 W to 18 W +/-10%
4.3.	Power Supply Unit	Driver included
4.4.	Power Cord	Øest. da 5mm a 12mm

Date	Verified by	Approved by	Page 1 of 2
24/09/2026			

**EP S.r.l.**

Via Del Commercio, 1 25039 Travagliato (BS) Italia
ph. +39 030 258 39 90 fax +39 0302584012
Cap. Soc. € 1.000.000,00 int.
VAT: 04678140981


**TECHNICAL
DATASHEET**

5.	MATERIALS	
5.1.	Body	Shock-resistant polycarbonate housing with hight painted finish
5.2.	Diffuser	Policarbonato ottico
5.3.	Hooks for wall mount and suspension	Stainless steel AISI 304
5.4.	Color	Matte white RAL 9010 and matte black RAL 9005

6.	WARRANTY	
6.1.	Optical Group Life	≥50.000 hr L90B10
6.2.	Warranty	2 years

7.	PHOTOMETRIC CHARACTERISTICS	
7.1.	Light source output	2800 lumen (face value) Ta=25°C
7.2.	Fitting output	2200 lumen +/-7%
7.3.	Type of optics	Diffusing

8.	PHOTOMETRIC CURVES	
----	--------------------	--



Date	Verified by	Approved by	Page 2 of 2
24/09/2026			